

Name of work: Construction of Kitchen for new feeding school at Baling PS

Bill of Quantity

Sl. #	Particular	Qty	Unit	Rate in figure	Rate in words	Amount
Sub - Structure						
1	Excavation in foundation trenches or drains not exceeding 1.5m in width or area 10 sq.m on plan, including dressing & ramming, disposal of surplus soil within 50m lead & 1.5m lift: Ordinary Soil	8.42	cu.m			
2	Providing and laying Hand packed stone filling or soling with stones	2.11	cu.m			
3	Providing and laying in position plain cement concrete excluding the cost of centering and shuttering - All work upto plinth level: 1:3:6 (1 cement : 3 sand : 6 graded crushed rock 20 mm nominal size)	1.40	cu.m			
4	Providing & laying in position reinforced cement concrete excluding the cost of centering, shuttering and reinforcement - all work upto plinth level: 1:2:4 (1 cement : 2 sand : 4 graded crushed rock 20 mm nominal size)	3.69	cu.m			
5	Providing & laying in position reinforced cement concrete work in plinth and skirting courses, fillets, columns , pillars, posts and struts upto floor five level excluding the cost of centering, shuttering and reinforcement: 1:2:4 (1 cement : 2 sand : 4 graded crushed rock 20 mm nominal size)	0.81	cu.m			

6	Providing & laying in position reinforced cement concrete work in beams, lintels, bands, plain window sills, staircases, spiral staircases upto floor five level excluding the cost of centering, shuttering and reinforcement: 1:2:4 (1 cement : 2 sand : 4 graded crushed rock 20 mm nominal size)	2.27	cu.m			
7	Providing & laying in position reinforced cement concrete work in suspended floor, roofs having slope upto 15o, landings balconies, shelves and chajjas upto floor five level excluding the cost of centering, shuttering and reinforcement: 1:2:4 (1 cement : 2 sand : 4 graded crushed rock 20 mm nominal size)	4.15	cu.m			
8	Providing & fixing Thermo-Mechanically Treated reinforcement bar (Yield Strength 500 MPa) for R.C.C work including cutting, bending, binding and placing in position complete	996.82	kg			
9	Providing & fixing centering and shuttering (formwork), including strutting, propping etc. and removal of formwork: Foundation and plinth etc	11.16	sq.m			
	Providing & fixing centering and shuttering (formwork), including strutting, propping etc. and removal of formwork: Columns, pillars, post, struts etc.	9.90	sq.m			

	Providing & fixing centering and shuttering (formwork), including strutting, propping etc. and removal of formwork:Lintels, beams, girders, bresummers, cantilevers etc.	24.94	sq.m			
	Providing & fixing centering and shuttering (formwork), including strutting, propping etc. and removal of formwork:Suspended floor, roof, landing, shelves and their supports, balconies, chajjas, etc	27.69	sq.m			
Super - Structure						
10	Providing & laying Second-Class Brick work in Foundation & Plinth: In cement mortar 1:4	14.17	cu.m			
11	Providing & laying Second-Class Half-brick Masonry (125 mm) in superstructure below floor 2 level: In cement mortar 1:3	19.15	sq.m			
12	Providing & laying Random Rubble Masonry with hard stone in foundation & plinth: In cement mortar 1:4	0.90	cu.m			
13	Providing & fixing in position dressed wood work in frames of doors, windows, clerestory windows and other frames, wrought and framed: Mixed Conifer	2.47	cu.m			
14	Providing & fixing M.S. round or square bars in window frames: 12 mm	26.70	kg			

15	Providing & fixing glass panes with putty, nails including remaining. broken glass panes: 4mm thick plain	6.30	sq.m			
16	Providing & fixing Battened door & window shutters 20mm, with ledges and braces (25 mm), including the cost of hinges: Mixed Conifer	4.51	sq.m			
17	Providing & fixing joists, including hoisting, applying wood preservative on unexposed surfaces: Mixed Conifer	0.66	cu.m			
18	Providing & fixing Mixed Conifer Flooring including fixing with iron screws etc. complete, excluding the cost of frame: 25mm thick, half-lapped	11.50	sq.m			
19	Providing & fixing Wire-gauze Shutters 25mm for doors & windows using galvanised M.S wire gauze 0.56mm dia wire including the cost of hinges: Mixed Conifer	18.00	sq.m			
20	Providing, making & fixing woodwork dressed in traditional cornices complete as per standard design in Mixed Conifer, including applying wood preservative on unexposed surfaces, excluding decorative painting (Measurement to be taken along the cornice and wall junction line): For single-storied structure including phana	26.20	m			

21	Providing & fixing M.S tower bolt (barrel type) with necessary screws etc. complete: 100mm	16.00	each			
	Providing & fixing M.S tower bolt (barrel type) with necessary screws etc. complete:150mm	2.00	each			
22	Providing & fixing M.S. sliding door bolt, bright finished, enamelled with necessary screws etc. complete: 200mm	2.00	each			
23	Providing & fixing M.S. handle with necessary screws etc. complete: 125mm	12.00	each			
24	Providing & fixing M.S. hook-and-eye with necessary screws etc. complete: 150mm	8.00	each			
Flooring and Trusses						
25	Pal cement concrete flooring 1:2:4, finished with floating coat of neat cement: 20mm aggregates, 75mm thick	29.50	sq.m			
26	Providing & fixing roof framing, in trusses, purlins, rafters, posts, post plates including hoisting, etc: Mixed Conifer	1.88	cu.m			

26	Providing & fixing Eaves board (225x25mm) with moulding fitted and fixed with necessary screws: Mixed Conifer	33.00	m			
28	Providing & fixing Corrugated Galvanised Iron (CGI) sheeting, including bolts, hooks and nuts 8mm dia. with bitumen and G.I limpet washers filled with white lead for connection, excluding the cost of purlins, rafter and trusses: 24g	78.78	sq.m			
29	Providing & fixing 600mm ridges or hips in plain G.I. including bolts, hooks and nuts 8mm dia G.I limpet and bitumen washers for connection: 24g.	10.10	m			
Finishing						
30	Providing & laying 20mm cement plaster: C.M 1:4	130.46	sq.m			
31	Providing & applying white or colour washing: White washing with lime, old work, two coats	130.46	sq.m			
32	Providing and laying 50mm thick Plinth Protection and grouted with fine sand mix including well rammed, finishing the top smooth: With cement concrete 1:3:6, 20mm aggregates, laid over 75mm thick layer of compacted gravel (40mm)	7.68	sq.m			

33	Constructing random rubble masonry open surface drain in cement mortar 1:6 including earth work in excavation, 100mm thick concrete base 1:5:10, 40 mm aggregate 25mm thick cement concrete 1:2:4, 12mm aggregate for filling haunches, including 20mm cement plaster with a floating coat of neat cement, disposal of surplus earth: 150 x 200mm depth	10.10	m			
34	Providing and Fixing PVC semi-circular gutter incl. fitting and ms clamp, etc: 180mm dia.	33.00	m			
35	Providing & fixing G.I. pipes including G.I. fittings & clamps & repair walls: 15mm	20.00	m			
36	15mm bib cock, vert, c.p knob	2.00	each			
37	Providing and Applying Bhutanese painting in accordance to Traditional Architectural norms: Rab and Ding	1.00	L/s			
		Total (Civil)				
		Electrical				
		G.Total				